

CSE 506: Operating Systems

Today's reading

Design challenges and trade-offs in a threading library

Nice practical tricks and system details
And some historical perspective on Linux evolution

CSE 506: Operating Systems

Threading review

• What is threading?

- Multiple threads of execution in one address space

- x86 hardware:


• One cr3 register and set of page tables shared by 2+ different register contexts otherwise (rip, rsp/stack, etc.)


- Linux:


• One mm_struct shared by several task_structs

- Does JOS support threading?

CSE 506: Operating Systems Stony Brook University Ok, but what is a thread library? · Threading APIs provided by libpthread.so Linux System Call libpthread.so pthread_create() clone(CLONE_FS|CLONE_IO| CLONE THREAD ...) pthread_mutex_lock(), pthread_cond_wait(),... futex() Thread-local storage arch_prctl() • System calls tend to be subtle, hard to program - Design reflects performance concerns The division of labor is part of the design!







Generalization — m:n model

Multiple application-level threads (m)

Multiplexed on n kernel-visible threads (m >= n)

N often number of CPUs

User Threading Complexity

• Lots of libc/libpthread changes

- Working around "unfriendly" kernel API

• Bookkeeping gets much more complicated

- Second scheduler

- Synchronization different

• Can do crude preemption using:

- Certain functions (locks)

- Timer signals from OS

- Signals

Why bother with user threading?

Context switching overheads
Finer-grained scheduling control
Blocking I/O

Context Switching Overheads

Recall: Forking a thread halves your time slice

Takes a few hundred cycles to get in/out of kernel

Plus cost of switching a thread

Time in the scheduler counts against your timeslice

threads, 1 CPU

If I can run the context switching code locally (avoiding trap overheads, etc), my threads get to run slightly longer!

Stack switching code works in userspace with few changes



CSE 506: Operating Systems

Finer-Grained Scheduling Control

- Example: Thread 1 has a lock, Thread 2 waiting for lock
 - Thread 1's quantum expired
 - Thread 2 just spinning until its quantum expires
 - Wouldn't it be nice to donate Thread 2's quantum to Thread 1?
 - Both threads will make faster progress!
- Similar problems with producer/consumer, barriers, etc.
- Deeper problem: Application's data flow and synchronization patterns hard for kernel to infer

13



CSE 506: Operating Systems

Blocking I/O

- I have 2 threads, they each get half of the application's quantum
 - If A blocks on I/O and B is using the CPU
 - B gets half the CPU time
 - A's quantum is "lost" (at least in some schedulers)
- Modern Linux scheduler:
 - A gets a priority boost
 - Maybe application cares more about B's CPU time...

14



CSE 506: Operating Systems

Blocking I/O and Events

- Events: abstraction for dealing with blocking I/O
- · Layered over a user-level scheduler
- Lots of literature on this topic if you are interested...

15



CSE 506: Operating Systems

Scheduler Activations

- · Better API for user-level threading
 - Not available on Linux
 - Some BSDs support(ed) scheduler activations
- On any blocking operation, kernel *upcalls* back to user scheduler
- · Eliminates most libc changes
 - Easier notification of blocking events
- User scheduler keeps kernel notified of how many runnable tasks it has (via system call)
 - Kernel allocates up to that many scheduler activations

16



CSE 506: Operating Systems

What is a scheduler activation?

- · Like a kernel thread:
 - A kernel stack and a user-mode stack
 - Represents the allocation of a CPU time slice
- · Not like a kernel thread:
 - Does not automatically resume a user thread
 - Goes to one of a few well-defined "upcalls"
 - New timeslice, Timeslice expired, Blocked SA, Unblocked SA
 Upcalls must be reentrant (called on many CPUs at same time)
 - User scheduler decides what to run

17



CSE 506: Operating Systems

Downsides of scheduler activations

- A random user thread gets preempted on every scheduling-related event
 - Not free
 - User scheduling must do better than kernel by a big enough margin to offset these overheads
- Moreover, the most important thread may be the one to get preempted, slowing down critical path
 - Potential optimization: communicate to kernel a preference for which activation gets preempted to notify of an event

Optional Reading on Scheduler Activations 18



CSE 506: Operating Systems

Back to NPTL

- Ultimately, a 1:1 model was adopted by Linux.
- · Whv?
 - Higher context switching overhead (lots of register copying and upcalls)
 - Difference of opinion between research and kernel communities about how inefficient kernel-level schedulers are. (claims about O(1) scheduling)
 - Way more complicated to maintain the code for m:n model. Much to be said for encapsulating kernel from thread library!

19



CSE 506: Operating Systems

Meta-observation

- Much of 90s OS research focused on giving programmers more control over performance
 - E.g., microkernels, extensible OSes, etc.
- Argument: clumsy heuristics or awkward abstractions are keeping me from getting full performance of my hardware
- · Some won the day, some didn't
 - High-performance databases generally get direct control over disk(s) rather than go through the file system

20



CSE 506: Operating Systems

User-threading in practice

- · Has come in and out of vogue
 - Correlated with how efficiently the OS creates and context switches threads
- Linux 2.4 Threading was really slow
 - User-level thread packages were hot
- Linux 2.6 Substantial effort went into tuning
 - E.g., Most JVMs abandoned user-threads

Stony Brook University

CSE 506: Operating Systems

Other issues to cover

- Signaling
 - Correctness
 - Performance (Synchronization)
- Manager thread
- List of all threads
- Other miscellaneous optimizations

22

21

Stony Brook University

CSE 506: Operating Systems

What was all the fuss about signals?

- 2 issues:
 - 1) The behavior of sending a signal to a multi-threaded process was not correct. And could never be implemented correctly with kernel-level tools (pre 2.6)
 - Correctness: Cannot implement POSIX standard
 - 2) Signals were also used to implement blocking synchronization. E.g., releasing a mutex meant sending a signal to the next blocked task to wake it up.
 - Performance: Ridiculously complicated and inefficient

Stony Brook University

CSE 506: Operating Systems

Issue 1: Signal correctness w/ threads

- Mostly solved by kernel assigning same PID to each thread
 - 2.4 assigned different PID to each thread
 - Different TID to distinguish them
- Problem with different PID?
 - POSIX says I should be able to send a signal to a multithreaded program and any unmasked thread will get the signal, even if the first thread has exited
- To deliver a signal kernel has to search each task in the process for an unmasked thread

24

23



CSE 506: Operating Systems

Issue 2: Performance

- · Solved by adoption of futexes
- · Essentially just a shared wait queue in the kernel
- Idea
 - Use an atomic instruction in user space to implement fast path for a lock (more in later lectures)
 - If task needs to block, ask the kernel to put you on a given futex wait queue
 - Task that releases the lock wakes up next task on the futex wait queue
- See optional reading on futexes for more details

25



CSE 506: Operating Systems

Manager Thread

- A lot of coordination (using signals) had to go through a manager thread
 - E.g., cleaning up stacks of dead threads
 - Scalability bottleneck
- Mostly eliminated with tweaks to kernel that facilitate decentralization:
 - The kernel handled several termination edge cases for threads
 - Kernel would write to a given memory location to allow lazy cleanup of per-thread data

26



CSE 506: Operating Systems

List of all threads

- · A pain to maintain
- Mostly eliminated, but still needed to eliminate some leaks in fork
- Generation counter is a useful trick for lazy deletion
 - Used in many systems
 - Idea: Transparently replace key "Foo" with "Foo:0". Upon deletion, require next creation to rename "Foo" to "Foo:
 1". Eliminates accidental use of stale data.

27

Stony Brook University

CSE 506: Operating Systems

Other misc. optimizations

- On super-computers, were hitting the 8k limit on segment descriptors
- · Where does the 8k limit come from?
 - Bits in the segment descriptor. Hardware-level limit
- How solved?
 - Essentially, kernel scheduler swaps them out if needed
 - Is this the common case?
 - No, expect 8k to be enough

28



CSE 506: Operating Systems

Optimizations

- Optimized exit performance for 100k threads from 15 minutes to 2 seconds!
- · PID space increased to 2 billion threads
 - /proc file system able to handle more than 64k processes

29

Stony Brook University

CSE 506: Operating Systems

Results

Big speedups! Yay!

30

Stony Brook University

CSE 506: Operating Systems

Summary

- Nice paper on the practical concerns and trade-offs in building a threading library
 - I enjoyed this reading very much
- Understand 1:1 vs. m:n model
 - User vs. kernel-level threading
- Understand other key implementation issues discussed in the paper

31